

## *S2 Instruments Electronic Fishing*

171 Greenwood Rd. Andover, Ma.  
(978) 475-6764 - Fax (978) 475-6764  
e-mail [info@makomagnet.com](mailto:info@makomagnet.com)



*Manufacturer of the finest  
electronic fishing lures*

**They hold a new concept in the leading technology of sport fishing.**

*Remember, if your looking for a competitive edge,  
get the MAGNET advantage. "*

**Instructions for trolling with the Tuna Teaser and Marlin Magnet**  
**If you have any question please call !!**

We suggest the following configurations for trolling. This permanent installation is to mount the unit ON the hull of the boat.

### **Mounting the unit on the hull (DO NOT CUT ANYTHING)**

**\*\*\*OPTION\*\*\*** A method we're investigating is to run a bead of quick dry 5200 on the flat surface of the unit. Allow some water to collect in the bilge area (about 3-4 inches). While placing the unit in the flooded area, rotate the unit to allow trapped air out from within the underside. Once that's done, sink the unit, apply some weights on top to make sure you have a tight seal, **TURN YOUR BILGE PUMP ON**, and allow the 5200 to dry (about 24 hrs).

This installation should take about 10 minutes of your time (not including curing time), and has proven to be VERY effective.

OR:

1) **The unit must be mounted below the water line.** This is to allow direct vibrations coupled from the unit to the portion of the hull that's in the water. Identify where the unit will be located on the hull of the boat.

2). Looking at the bottom of the unit (the aluminum ring) picture a face of a clock. Run a bead of silicone (or other sealant) from about 11 o'clock to about 1 o'clock. This will leave a slight opening. Mount the unit to the boat surface making sure the silicone makes a good contact. Let the silicone cure.

3) Once cured, place a small tube in the opening that was left UN-sealed (you can also use a hypodermic), fill the gap between the unit and the hull of the boat with any fluid (you can even use sea water). The purpose of this is to eliminate as much as the air as possible. When the tube overflows, remove the tube, and seal off that part with silicone. Unit is now mounted and ready for use.

**The removal of air is important**, air is compressible and will reduce the overall efficiency. By replacing the air with oil (or other fluid), you are assured a solid medium that will couple 100% of the energy directly to the surface of the hull, and in turn to the water.

4) **Electrical:** Simply attach the black wire to the negative side of your battery, and the red (sometimes white) wire to the positive side of your battery, DAMAGE WILL OCCUR IF YOU REVERSE. You should now hear the output of the unit.

5) **Output:** Testing the output of the ATTRACTOR. Attach the cables to the battery per above, you will hear the output sound vibration.

This installation should take less than an hour of your time (not including curing time), and has proven to be VERY effective.

[Click here for "Drifting Instructions"](#)

---

| [Home](#) | [About](#) | [Braggin](#) | [Products](#) | [Main](#) | [Contact](#) | [links](#) |

---

[Frames On](#) [Frames Off](#)

---